
OL.MI®
INNOVAZIONI TECNOLOGICHE

液压自闭暗藏铰链
Closer/Hinge Hydraulic Unit





普通暗藏铰链
Plain Pivot Hinge






产品特点：

- 意大利原产进口；
- 每套含1只液压自闭铰链及1只普通承重暗藏铰链；
- 集隐藏安装、三维可调及液压缓冲自闭功能于一体；
- 关门速度和闭锁速度可调；关门力度可调；
- 适用于平口门，
- 1组（2只）合页最大承重100KG；
- 最大开门角度125°；
- 适用最小门厚40mm，适用最大门宽1200mm；

STRONG, SELF-CLOSING PERFORMANCE



* **CAUTION**: A floor-mounted **DOOR STOP** is recommended to prevent a door opening beyond 125° (see above diagram). Forcing a door beyond a 125° opening may damage closer and void Warranty.



MODEL	DESCRIPTION	SELF CLOSES	MAX ANGLE OPENING	LOAD BEARING CAPACITY	MINIMUM DOOR THICKNESS	MAX DOOR WIDTH
KIT REI CM / REI SM	Concealed Hydraulic Door Closer and Hinge	125°	125°	100 kg	40mm	1200mm
REI SM	Plain Door Hinge	n/a	125°	100 kg	40mm	1200mm

购买咨询：
北京中意信诚贸易有限公司
Tel:13910114747

OL.MI®
INNOVAZIONI TECNOLOGICHE

Closer/Hinge Hydraulic Unit



Plain Pivot Hinge



REF	PART ADJUSTMENT	UNIT	RANGE
1	Height	Both	+/-2 mm with 1mm steps
2	Lateral	Both	+/-1.25mm
3	Depth and Inclination	Both	Gap between post and door leaf is adjustable from 2mm to 6mm
4	Door closing force	Master	1470N - 1755N
5	Final snap-close action	Master	12° - 0°
6	Opening angle	Master	Steps at 60°, 80°, 100° and 125°
7	Self-closing	Master	125° to 0°

合页调节 ADJUSTMENTS OF HINGE:

1、垂直方向可调 ± 2 mm;
2、前后方向可调 ± 1.25 mm;
3、水平方向可调 -1.5/+2.5 mm;

闭门功能调节 ADJUSTMENTS OF CLOSING DEVICE:


4、关门力度 1470N-1755N **可调;**
5、最后关门行程12°-0° **闭锁速度可调;**
6、最大开门角度60°、80°、100°、125°**四档可调;**
7、关门速度可调;


门框侧
Frame part


门扇侧
Sash part





OL.MI®
INNOVAZIONI TECNOLOGICHE


























门框部分 Frame Part




液压铰链门扇部分 Sash Part




门框部分 Frame Part



普通铰链门扇部分 Sash Part







购买咨询：
北京中意信诚贸易有限公司
Tel:13910114747


液压自闭暗藏合页
Self-Closing Concealed Hinge

液压自闭铰链调节 Hinge adjustments with self-closing device





无液压铰链调节 Hinge adjustments without self-closing device



购买咨询：
北京中意信诚贸易有限公司
Tel:13910114747